

USE

The function of these belt conveyors is to transport any type of product both horizontally and inclined.

OPERATION

The product enters by gravity into a hopper and falls on a rubber-PVC or other material carpet; the conveyor tension is through two drums (towing and neutral); conveyor running rollers are positioned at a variable pitch which changes depending on the material and weight to be supported.


MANUFACTURING

- Metal sheet with galvanised metal sheet sections framework support
- Hemmed edge metal sheet tanker, bolted among the various elements that make it up
- Conveyor handling drums
- Product inlet hopper
- · Direct or belts drive














DETAILS

- 01) Spondaflex conveyor
- 02) Plane conveyor
- 03) Conveyor sliding roller
- 04) Plane conveyor transporter plan on EVO plant
- 05) SF model transporter feeding seed selection plant
- 06) Conveyor detail on TAN-SF C model
- 07) Drive TAN-L tail
- 08) TAN-SF C model truck-mounted conveyor






TAN-L



MODELS	CAPACITY t/h	POWER kW	LENGHT mm	A mm	B mm
TAN-L 20/L3000	5	0,75	3000	345	150
TAN-L 20/L4000	5	0,75	4000	345	150
TAN-L 20/L5000	5	0,75	5000	345	150
TAN-L 20/L6000	5	1,1	6000	345	150
TAN-L 50/L3000	15	1,1	3000	545	250
TAN-L 50/L4000	15	1,1	4000	545	250
TAN-L 50/L5000	15	1,1	5000	545	250
TAN-L 50/L6000	15	1,5	6000	545	250
TAN-SF 30/L3000	5	0,75	3000	490	310
TAN-SF 30/L4000	5	0,75	4000	490	310
TAN-SF 30/L5000	5	1,1	5000	490	310
TAN-SF 30/L6000	5	1,1	6000	490	310
TAN-SF 50/L3000	15	1,5	3000	690	410
TAN-SF 50/L4000	15	1,5	4000	690	410
TAN-SF 50/L5000	15	1,5	5000	690	410
TAN-SF 50/L6000	15	2,2	6000	690	410

NB: SF versions are equipped with special tape "spondaflex". These versions are available with belt at an angle. Capacity calculated with product ps $0.78 \text{ t} / \text{m}^3$ and $30 ^\circ$ inclination.





ZANIN F.IIi s.r.l.

Viale delle Industrie, 1 - 31032 Casale sul Sile (TV) - Italy Tel. +39 0422 785444 - Fax +39 0422 785805 www.zanin-italia.com info@zanin-italia.com



© 2015 ZANIN F.III - WARNING: DATA NOT BINDING, PLEASE REFER TO THE TECHNICAL DATA RELEASED DIRECTLY FROM ZANIN F.LLI

